



Young Regulator Co.

7100 Krick Rd • Walton Hills, OH 44146
 P: 440-232-9700 • F: 440-232-8266
www.youngregulator.com

Submit 3150 – 1-10

Model 3150

*Rectangular Motorized Damper
 Power Open / Spring Close - 24V Standard*

Application and Design

The Young Regulator Model 3150 is a motorized, rectangular, opposed blade damper. It is constructed of an extruded aluminum frame and blades, stainless steel slide, and a 24V (standard) or 110V (optional) spring return motor. Applications include zone control, outside air, exhaust air vents, although they may be used to control air in any system duct. It can be made to power open and spring return closed, or power close and spring return open.



STANDARD CONSTRUCTION	
Frame	.050 Aluminum Extrusion with Reinforcing Channels
Blade	.050 Aluminum Extrusion with Reinforcing Channels
Mounting Plate	5" Wide x Damper Height
Slide	Stainless Steel
Blade Bushing	Individual Synthetic
Low Leak Seals	Not Available
SIZE INFORMATION Damper 3/16" undersized high & wide	
Frame Width	2 1/8" Wide
Blade Width	1.438" - Contained within frame
Max Size	24" x 14"
Min Size	3" x 3"

ACTUATOR (24V STANDARD)	
Special windings and heavy-duty steel gearing provide for long life and easy spring return operation. Cross pin on motor shaft provides positive direct drive to damper without a coupling or setscrews and allows for quick and easy motor change.	
Volts	24V
Watts	6
VA	10
Amp	.45
Timing	15 Sec Powered. 5 Sec Return.
Torque	35 in. oz.
Adjustable minimum air	
OPTIONS	
Transformers / Thermostats	Bottom Mount
110V Optional	PC/SO

QUANTITY	WIDE	HIGH	NOTES

PROJECT	LOCATION
CONTRACTOR	DESIGN SPECIFIER